

YOUR BARRIER OF PROTECTION AGAINST THE ELEMENTS.



Commercial grade for severe weather.

| PROLinx BUILDING WRAP | <i>Select</i> | <i>Drain</i> | <i>Advantage</i> | <i>Plus HP</i> |
|---------------------------------|---------------|--------------|------------------|----------------|
| Meets Building Code | ☑ | ☑ | ☑ | ☑ |
| Energy Efficient | ☑ | ☑ | ☑ | ☑ |
| Optimal UV Resistance | ☑ | ☑ | ☑ | ☑ |
| Superior Tear Strength | ☑ | ☑ | ☑ | ☑ |
| BROADCAST™ Custom Printing | ☑ | ☑ | ☑ | ☑ |
| Enhanced Drainage Capability | | ☑ | ☑ | |
| Certified Air Barrier | | ☑ | ☑ | ☑ |
| More Robust Water Resistance | | ☑ | ☑ | ☑ |
| 10-Year Limited Warranty | ☑ | ☑ | ☑ | ☑ |



PROLinx® Advantage is a commercial-grade building wrap, engineered from non-perforated cross woven fabrics. Providing the highest real-world resistance to severe weather and wind driven rain, it is well-suited for demanding residential and commercial projects.

PROLinx Advantage is a recognized air barrier material that allows for a balanced transfer of moisture vapor, creating a healthier and more energy-efficient structure.

PROLinx Advantage is available with BROADCAST® custom printed advertising. Now you can custom print **PROLinx Advantage** in full color with alternating messages in the industry's smallest minimum quantities.

Strength: PROLinx Advantage provides maximum durability with high resistance to tearing.

Industry Leading Weather Protection: PROLinx Advantage exhibits class-leading resistance to moisture and limits air movement within the wall cavity.

Breathability: PROLinx Advantage is engineered to slow inward moisture vapor drive more than higher breathing building wraps.

Energy Efficiency: PROLinx Advantage is recognized as an air barrier material, which qualifies it as an "Eligible Building Envelope Component" under section 25C of the American Recovery and Reinvestment Tax Act of 2009. It also qualifies its user for a Federal Tax Credit.

Simple Application: Lightweight, yet durable, PROLinx Advantage is translucent which makes locating studs, openings, and corners quick and easy.

Meets Building Codes: PROLinx Advantage is rated for commercial projects and offers excellent performance in residential applications. It meets or exceeds applicable building codes for water-resistant barriers and air barriers, creating a healthier, more energy-efficient building.

UV Exposure Rating: PROLinx Advantage has a 50% longer UV exposure rating than other building wrap brands, and may be left exposed or up to 180 days.

PROLinx Flashing and Sheathing Tapes are also available. 10-Year Limited System Warranty

Broadcast and WrapLab are a registered service mark and a trademark, respectively, of Jumpstart Consultants, Inc. International patents pending for the WrapLab custom print application.



Advantage

Typical Physical Properties

| Property | Standard | UoM | Typical Result [†] |
|-----------------------------------|---------------------|------------------------------|-----------------------------|
| Basis Weight | ASTM D 5261 | g/m ² | 90 |
| Breaking Tensile Strength (MD/CD) | ASTM D 882 | lbs/inch | 71/50 |
| Water Vapor Transmission Rate | ASTM E 96, Method A | g/m ² /24 hours | 84 |
| Water Vapor Permeance | ASTM E 96, Method A | perms | 12 |
| Water Penetration Resistance | AATCC 127 | cm H ₂ O | 500 |
| Water Resistance | ASTM D 779 | minutes | 60 |
| Water Ponding | ASTM E 2556, A 1.1 | Pass/Fail | Pass |
| Air Resistance | ASTM E 2178 | L/sec/m ² @ 75 Pa | 0.01 |
| Flame Spread Index | ASTM E 84 | Class | A |
| Smoke Developed Index | ASTM E 84 | Class | A |
| Ultraviolet Light (UV) Exposure | Internal | Days | 180 |

[†] Test data is based on average results and is not limiting specifications. Normal manufacturing variation may produce results above or below typical data and should not be considered or interpreted as minimum or maximum values.

WARRANTY INFORMATION

A ten- (10-) year limited warranty applies to **PROLinx**[®] **Advantage** building wrap. To obtain a copy of this warranty, please visit bluelinxco.com. No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

PRECAUTIONS

Warning: Protect from high heat or other ignition sources during shipment, storage and application.

STORAGE

Take care to protect **PROLinx** building wrap from exposure to direct sunlight during storage. It is recommended that building wrap to be stored inside or under cover.

ROLL SIZES*

| | | | |
|-----------|------------|-------------|-------------|
| 3' x 100' | 3' x 150' | 4.5' x 100' | 4.5' x 150' |
| 5' x 100' | 5' x 150' | 9' x 100' | 9' x 150' |
| 9' x 195' | 10' x 100' | 10' x 150' | 10' x 195' |

*Not all rolls available for BROADCAST custom printing, ask your sales representative for more details.



is the finest in the industry. It turns passersby into an audience, and a building into a billboard – a vivid, multi-colored multi-messaging platform with endless revenue generating possibilities. BROADCAST custom printing leads the industry with the following features:

Full Color:

A full range of vivid colors.

Maximum-size:

The largest printing area available.

Alternating Messages & Images:

Select multiple messages for your building wrap.

Flexible Order Size:

Print and order minimums as small as eleven rolls and as large as needed.

Visit our WRAPLAB™ at prolinx.customprintwrap.com

Call your BlueLinx representative to find out how custom printing can expand your business!

