

# YOUR BARRIER OF PROTECTION AGAINST THE ELEMENTS.



Enhanced drainage capability for severe weather.

<b>PROLinx</b> BUILDING WRAP	<i>Select</i>	<i>Drain</i>	<i>Advantage</i>	<i>Plus HP</i>
Meets Building Code	☑	☑	☑	☑
Energy Efficient	☑	☑	☑	☑
Optimal UV Resistance	☑	☑	☑	☑
Superior Tear Strength	☑	☑	☑	☑
BROADCAST™ Custom Printing	☑	☑	☑	☑
Enhanced Drainage Capability		☑	☑	
Certified Air Barrier		☑	☑	☑
More Robust Water Resistance		☑	☑	☑
<b>10-Year Limited Warranty</b>	☑	☑	☑	☑



**PROLinx® Drain** is designed for severe weather protection, maximum drainage, and balanced breathability under fiber-cement, brick, vinyl, stucco, hardboard, metal, stone, and wood sidings. It promotes drainage in all directions for faster, more complete drying and easy installation. **PROLinx Drain** is UV-stabilized and may be left exposed for up to 120 days. To learn how to transform your PROLinx Drain into a multi-colored, multi-messaging space with endless revenue-generating possibilities, visit our custom printing page!

**PROLinx Drain** is available with BROADCAST® custom printed advertising. Now you can custom print **PROLinx Drain** in full color with alternating messages in the industry's smallest minimum quantities.

**Drainage Barrier:** PROLinx Drain combines the benefits of a rainscreen and building wrap to promote moisture movement away from the wall.

**Durable Drainage Surface:** PROLinx Drain's durable drainage surface does not collapse or flatten when siding is installed.

**Breathable:** PROLinx Drain provides superior resistance to weather, exhibits high moisture vapor transfer rates and is a recognized air-barrier material by ICC-ES.

**Meets Building Codes:** PROLinx Drain is rated for commercial projects. It meets or exceeds applicable building codes for water-resistant barriers and drainage rates, creating a healthy, energy-efficient building.

**Stable:** PROLinx Drain is treated to resist excessive degradation from normal exposure to ultraviolet light and may be left exposed for up to 120 days.

**PROLinx Flashing and Sheathing Tapes are also available. 10-Year Limited System Warranty**

Broadcast and WrapLab are a registered service mark and a trademark, respectively, of Jumpstart Consultants, Inc. International patents pending for the WrapLab custom print application.



### Typical Physical Properties

Property	Standard	UoM	Typical Result <sup>†</sup>
Basis Weight	ASTM D 5261	g/m <sup>2</sup>	72
Breaking Strength (MD/CD)	ASTM D 882	lbs/inch	30/30
Drainage Efficiency <sup>3</sup>	ASTM E 2273	% Efficiency	95
Water Vapor Transmission Rate	ASTM E 96, Method A	g/m <sup>2</sup> /24 hours	392
Water Vapor Permeance	ASTM E 96, Method A	perms	56
Water Penetration Resistance	AATCC 127	cm H <sub>2</sub> O	186
Water Resistance	ASTM D 779	minutes	60
Air Resistance	ASTM E 2178	Lsec/m <sup>2</sup> @ 75 Pa	< 0.02
Flame Spread Index	ASTM E 84	Class	A
Smoke Developed Index	ASTM E 84	Class	A
Ultraviolet Light (UV) Exposure	Internal	Days	120

<sup>†</sup> Results reflect typical properties of control/non-conditioned specimens. Values should not be interpreted as limiting specifications and will vary within typical manufacturing tolerances.

### WARRANTY INFORMATION

A ten- (10-) year limited warranty applies to **PROLinx<sup>®</sup> Drain** building wrap. To obtain a copy of this warranty, please visit [bluelinxco.com](http://bluelinxco.com). No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

### PRECAUTIONS

Warning: Protect from high heat or other ignition sources during shipment, storage and application.

### STORAGE

Take care to protect PROLinx building wrap from exposure to direct sunlight during storage. It is recommended that building wrap to be stored inside or under cover.

### ROLL SIZES\*

3' x 100', 4.5' x 100', 5' x 100', 9' x 100', 10' x 100',  
 3' x 150', 4.5' x 150', 5' x 150', 9' x 150', 10' x 150',  
 9' x 195', 10' x 195'

\*Not all rolls available for BROADCAST custom printing, ask your sales representative for more details.



is the finest in the industry. It turns passersby into an audience, and a building into a billboard – a vivid, multi-colored multi-messaging platform with endless revenue generating possibilities. BROADCAST custom printing leads the industry with the following features:

### Full Color:

A full range of vivid colors.

### Maximum-size:

The largest printing area available.

### Alternating Messages & Images:

Select multiple messages for your building wrap.

### Flexible Order Size:

Orders as small as eight rolls, and as large as needed.

Visit our WRAPLAB™ at

[prolinx.customprintwrap.com](http://prolinx.customprintwrap.com)

Call your BlueLinx representative to find out how custom printing can expand your business!

