

*The feel of felt.  
The superiority of  
synthetics.*

BlueLinXCo.com



## **PROLinX**<sup>®</sup> *Synthetic* UDL 20

*Built to last — just like everything  
you build.*

Made from 100% synthetic materials, PROLinX Synthetic UDL 20 fits the perfect combination you're looking for: Strength, durability, and ease of installation. PROLinX Synthetic UDL 20 is available with BROADCAST<sup>®</sup> printing to display any logo or advertising message — and can be ordered in the industry's smallest quantities.

### Benefits:

- **Easier, safer, and faster installation** due to its low-slip back and non-woven walking surface
- **Better handling and compatible** with standard roof nails
- **Stronger than felt** — it's 25x stronger than 15 lb. felt and 12x stronger than 30 lb. fel
- **Absorbs less heat** due to its gray color, making Afor a comfortable working surface
- **Provides more coverage** per course that 15 and 30 lb. felt
- **Flexible and easy to install** in cold climates
- **Will not wrinkle or absorb water** because of its superior lay-flat properties

BROADCAST<sup>®</sup> and WrapLab<sup>®</sup> are a registered service mark and a trademark, respectively, of Jumpstart Consultants, Inc. International patents pending for the WrapLab custom print application.

**BlueLinX**   
America's Building Products Distributor

## Warranty Information

A twenty (20) year limited warranty applies to PROLinx® Synthetic UDL 20. To obtain a copy of this warranty, please visit [bluelinxco.com](http://bluelinxco.com). No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

## Precautions

PROLinx Synthetic UDL 20 can be exposed to ultraviolet conditions for up to 90 days. Local weather conditions may require a shorter exposure period; contact BlueLinx for details.

## Package Specifications

Roll Dimension	40" x 300'	56 rolls per pallet
	60" x 200'	48 rolls per pallet
Weight per roll	20.2 lbs	
Coverage per roll	10 sq	
Pallet Weight	1200 lbs	

## Code & Standard Compliance

- Intertek CCRR-0310
- ASTM D226 Type I & II
- ASTM D4869
- ASTM E108
- CSA A 123.3 Type 1 & 2
- FBC #17873
- Texas Dept. of Insurance (TDI)

## World-class underlayment. Localized service.

Covering most of the metro areas in the contiguous 48 states, BlueLinx has branches ready to fulfill your order. Our representatives know the geography of the markets you're working in, and product delivery is never far away. PROLinx can be ordered in the industry's smallest quantities and we can deliver your order along with other BlueLinx products for your convenience.

### Typical Physical Properties

Property & Standard	PROLinx UDL 20 Typical Result	ASTM #15 Felt Typical Result	ASTM #30 Felt Typical Result
Permeability ASTM	0.1 perms	5 perms	1.75 perms
Water Transmission D4869	Pass	Pass	Pass
Tear Strength D4533	MD 33 lbs / CD 24 lbs	2.2 lbs / 4 lbs	4 lbs / 2 lbs
Tensile Strength D751	MC 95 lbs / CD 85 lbs	54 lbs / 29 lbs	70 lbs / 38 lbs
Burst Strength D751	160 psi	35 psi	62 psi
Elongation D751	20%	3%	2%
Weight per Square D5261	1.96 lbs	11.2 lbs	27.5 lbs
Nominal Thickness D1777	6.2 mils	21 mils	60 mils
Temperature Range (Internal)	-70°F to 212°F	No value offered	No value offered

*Results reflect typical properties of control/non-conditioned specimens. Values should not be interpreted as limiting specifications and will vary within typical manufacturing tolerances.*

**For application instructions, visit [BlueLinxCo.com](http://BlueLinxCo.com)**



**BROADCAST®**  
CUSTOM PRINTED  
ADVERTISING



## Make a bold statement. Let everyone see it.

Turn your building into a billboard. BROADCAST® Custom Printing lets contractors, builders, lenders, or anyone else put their logo or advertising message on any PROLinx underlayment product. Print with multiple, vivid colors on a large surface area, with a small roll order minimum.

See how it works by visiting [WRAPLAB®](http://WRAPLAB®) at [prolinxudl.customprintwrap.com](http://prolinxudl.customprintwrap.com)

### Full Color:

A full range of vivid colors.

### Maximum-size:

The largest printing area available.

### Alternating Messages & Images:

Select multiple messages for your underlayment.

### Flexible Order Size:

Industry's smallest minimum quantities available.

*Call your local BlueLinx representative to find out how custom printing can expand your business!*



**BlueLinxCo.com**

PROLinx UDL20 / 1-2021